



CE

---

Power	<b>18 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>2000 lm (360°)</b>	Colour temperature	<b>4000 K</b>
Colour of light	<b>Neutral white</b>	Beam angle	<b>115 °</b>
Degree of protection (IP)	<b>IP54</b>		


---



 Declaration of Conformity

**Technical data:**

Code	SLI031034NW_PW_CZUJNIK
Power	18 W
Nominal current	125 mA
Voltage	230 V
Energy consumption	18 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.6
Useful luminous flux*	2000 lm (360°)
Luminous flux**	1200 lm (360°)
Lamp efficacy	111 lm/W
Luminous intensity	760 cd
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	115 °
RA	>80
Light source included	+
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 +40 °
Lifespan	17000 h
Housing material	TWORZYWO SZTUCZNE
Degree of protection (IP)	IP54
Colour	White
Dimension (AxBxC)	250x52 mm
For use	Inside
Assembly method	On the ceiling
Application	Inside
Made in	PRC
Other	MV Sensor ,



\*applies to the LED source used. \*\*Luminaire luminous flux