

DURE 3 18W downlight



CE

| | | | |
|---------------------------|-----------------------|-----------------|--------------|
| Power | 18 W | Voltage | 230 V |
| Luminous flux* | 2200 lm (360°) | Colour of light | CW |
| Beam angle | 110 ° | IK | 6 |
| Degree of protection (IP) | IP54 | | |



See more on dedicated page [➔](#)



 Declaration of Conformity

Technical data:

| | |
|------------------------------|----------------|
| Code | SLI043011CW_PW |
| Power | 18 W |
| Nominal current | 135 mA |
| Voltage | 230 V |
| Energy efficiency class | E |
| Energy consumption | 18 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | II |
| Power factor | 0.6 |
| Useful luminous flux* | 2200 lm (360°) |
| Luminous flux** | 1600 lm (360°) |
| Lamp efficacy | 123 lm/W |
| Colour of light | CW |
| Beam angle | 110 ° |
| RA | 80 |
| Uniformity of color SDCM max | 5 |
| Working temperature range | -20/+40 ° |
| Lifespan | 17000 h |
| Housing material | PC+PS |
| IK | 6 |
| Degree of protection (IP) | IP54 |
| Colour | White |
| Dimension (AxBxC) | 170x170x34 mm |
| Mounting hole | 145x145 mm |
| Weight | 0.17 kg |
| For use | Inside |
| Assembly method | Recessed |
| Application | INT |
| Made in | PRC |



*applies to the LED source used. **Luminaire luminous flux