




Power	<b>12 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>1600 lm (360°)</b>	Colour temperature	<b>4000 K</b>
Light colour	<b>Neutral white</b>	Beam angle	<b>110 °</b>
IK	<b>6</b>	Protection class	<b>IP44</b>



See more on dedicated page 



 User manual

**Technical data:**

Product code	SLI043013NW_PW
Power	12 W
Nominal current	68 mA
Voltage	230 V
Energy consumption	12 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power factor	0.8
Useful luminous flux*	1600 lm (360°)
Luminous flux**	1200 lm (360°)
Light efficiency	133 lm/W
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	110 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	PA6+Aluminum
IK	6
Protection class	IP44
Colour	White
Dimension (axbxc)	140x30 mm
Mounting hole	110 mm
For use	Inside
Assembly method	Recessed
Application	INT
Made in	PRC



\*Applies to the LED source used. \*\*Luminaire luminous flux